



B2250H

(Reflective Sheet, Glossy)

Product Introduction:

B2250H. It is popular appropriate for art canvas.

Product Description:



Material: Polyester with Micro-porous coating

Size: 36''~60'' width * 30M length

Product Application:

Indoor/Outdoor for frame or advertising.

Technical Data:

Test Items	Units	Test method	Average value
Finished Products Weight	gsm		220
Whiteness		CIZ Ganz	60
Gloss Rate (60°)	%	ISO2813	50%
Opacity	%	ISO2471	80
Dimensional stability	mm	DIN 38464	≤0.1
Tensile Strength-MD	N/50mm	DIN53354	≥1000
Tensile Strength-CD	N/50mm	DIN53354	≥1000
Tearing Strength-MD	N	DIN53356	≥180
Tearing Strength-CD	N	DIN53356	≥210
Service Temperature	°C		-20~+70
Best Printing Temperature	°C		23±2; 50±5%RH
Ink temperature	°C		18~28
Preheating temperature	°C		30
Shelf Life	Stored at 20-25 °C/50-55 % RH		1 year
Durability, unprinted	Indoor at 20-25 °C/50-55 % RH		2 year
Ink recommendations	 Eco-solvent  Solvent		

*Testing condition: Indoor temperature 23°C, Relative Humidity 50%.



Note:

Information on physical and chemical characteristics is based upon tests we believe to be reliable.

The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty.

Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change.

Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking.