



DRAGON WAY DI MONICA PIERALISI
VIALE G. PIERALISI N 5
60030 MONSANO (AN) ITALY
P.IVA 02856370420 COD.FISC. PRLMNC78E70C615B
TEL. +39 0731 60083 E-mail: info@dragonway.it

M09G1

(Floor Lamination Film, Matte)

Product Introduction:

M09G1 is a Matte lamination film with “cold” solvent acrylic pressure sensitive permanent adhesive. Designed to protect ground signs with excellent anti slip performance

Product Description:

PVC Film: Matte Monomeric PVC film, 200 micron (Including glue)

Adhesive: Permanent clear glue

Liner: One side PE coated white paper, 140gsm

Size: 36”, 42”, 50”, 60” width * 50M length

Product Features:

Protect and enhance the artistic effect of graphics

Excellent anti slip performance.

High transparence PVC film and glue.

Product Application:

Indoor media protection and decoration

Technical Data:

Test Items	Units	Test method	Average value
Thickness-PVC	Micron	ISO534	175±5
Weight-Liner	g/m ²	GB4669-1995	140±5
Gloss Rate-60 °	%	ISO2813	8±10%
Initial Adhesion	N/25mm	FTM-1	≥8
Adhesion 24h-180° peel	N/25mm	FTM-1	≥10
Opacity	%	ISO2471	9.5
Dimensional stability	mm	DIN 38464	≤1.0
Tensile Strength-MD	N/50mm	DIN53354	≥60
Tensile Strength-CD	N/50mm	DIN53354	≥40
Tearing Strength-MD	N	DIN53356	≥8
Tearing Strength-CD	N	DIN53356	≥12
Flammability			Self extinguishing
Service Temperature	°C		-20~+70
Shelf Life	Stored at 20-25 °C/50-55 % RH		1 year
Durability, unprinted	Vertical exposure		1 year

Notes:

Information on physical and chemical characteristics is based upon tests we believe to be reliable.

The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty.

Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change.

The durability, removal, stability is based on East China exposure conditions.

Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking.

*Testing condition: Indoor temperature 23 °C, Relative Humidity 50%.



+39 0731 60083



WWW.DRAGONWAY.IT
INFO@DRAGONWAY.IT



VIALE G. PIERALISI N. 5
 60030 MONSANO (AN) ITALY